

REPLACEMENT GLASS INSTRUCTIONS for UPPER OR LOWER GLASS

**** READ ALL INSTRUCTIONS FIRST BEFORE PROCEEDING****
CAUTION: Always wear eye and hand protection when replacing glass.

Please note: If the backing plate is missing behind the upper glass, then you will need a complete new mirror head and will not be able to replace the glass only.

Backing Plate



- 1) Locate appropriate mirror clip depending if your replacing flat glass or convex glass as shown in **view A-A**.
- 2) Manually rotate mirror glass to better expose mirror clip and pry off clip with small screw driver at both ends of clip as shown below. Discard clip.
- 3) Remove broken glass (if held in with sticky pads) by prying out with screw driver being careful of sharp edges.
- 4) Once glass is removed, unclip heating element wires located at back of glass taking care that wires do not slip back inside of mirror housing.
- 5) Attach heating element wires to new glass and assemble glass into mirror housing being sure that glass is placed under retaining lip at opposite end of mirror clip as shown below.
- 6) Assemble mirror clip (included in kit) to end of glass housing as shown in **view C-C** by inserting clip into receiver until clip snaps into place. **Note:** Mirror glass clips can be removed as described above or if clip retainer is exposed as shown in **view B-B**, pinch hooks together with needle nose pliers at points indicated by arrows and pull glass clip out. Follow steps 4 thru 6.

